



The V Series table base is designed to fit into any budget without sacrificing performance. This base includes Grand Stands no crossbar design and the leading technology from LINAK, the world's leading actuator manufacturer. Everything in the LINAK system is engineered and built by or built for LINAK to perform in a LINAK system. The tightest tolerances and the best engineering assures your base will perform for years.

Proven Technology

No Crossbar

Tightest Tolerances

BOTH V2 AND V3 FEATURE:

- ▶ All solid state technology smooth travel and proven soft stop and start
- ▶ Superior design for true no crossbar design
- ▶ Less than 0.1W standby power draw
- ▶ 175 pounds lift per leg, 800 newton lift
- ▶ Can be configured for 2, 3 or 4 legs
- ▶ 23.5" and 10" Foot Kits available with mounting bracket set
- ▶ Meets BIFMA and UL & ETL recognized

V2 - TWO STAGE BASE

- ▶ 20" of height range. Starting at 25 3/4" or 26 3/4" (excludes surface) fits filing under the surface
- ▶ Software based Impact detection
- ▶ 1.7" travel per second standard, can be configured for a different speed

V3 - THREE STAGE BASE

- ▶ Meets ANSIHFES 25.5" of height range. Starting at 21.25" or 48.75" (excludes surface)
- ▶ PIEZO Impact detection
- ▶ 3.15" travel per second standard speed.



2-Leg Base:

V2-2L-F24TC-Switch-Color (for 24 and 30" deep surfaces)

V3-2L-F24TC-Switch-Color (for 24 and 30" deep surfaces)

3-Leg Base:

V2-3L-F24/10TC-Switch-Color (for 24" and 30" deep surfaces)

V3-3L-F24/10TC-Switch-Color (for 24" and 30" deep surfaces)

V2 TWO STAGE BASE

Software Based
impact detection

20" height range from
25 3/4" or 26 3/4" from
the floor to the top of
the base

V3 THREE STAGE BASE

PIEZO hardware
impact detection

25.5" height range from
20 3/4" or 21 3/4" from the
floor to the top of the
base.

T Style (with drop-in)
only available

BIFMA Certified



FINISHES



White



Silver



Black

Custom
finishes
available

